


# Not a "UT18 replacement kit" only **V5**

Cord-grips are supplied loose: small bag in the carton (versions with heatsink only)  
 Round shape only available for versions without heatsink



UV-glued protection cover against electrical sock; holes for air circulation

## Comparison with Fluorescent lamps:

Type	Description	Nominal light output lm	Lifetime h	Light intensity at 1m - Cd C	Ballast Losses W	System consumption W	Efficiency lm/W	Efficiency cd/W
8,7W	Led board	630	>30.000	268,0	-	8,7	72,4	30,8
13W	Led board	940	>30.000	392,0	-	13	72,3	30,2
17W	Round led board	1300	>30.000	451,0	-	17	76,5	26,5
23W	Energy Saving	1340	10.000	148,0	5	28	47,9	5,3
7W	Fluorescent +KVG	400	9.000	105,0	7	14	28,6	7,5
9W	Fluorescent +KVG	600	9.000	147,0	7	16	37,5	9,2
11W	Fluorescent +KVG	900	9.000	227,0	7	18	50,0	12,6
13W	Fluorescent +KVG	900	9.000	140,0	6	19	47,4	7,4
18W	Fluorescent +KVG	1200	9.000	170,0	8	26	46,2	6,5
26W	Fluorescent +KVG	1800	9.000	268,0	8	34	52,9	7,9

